



MATERIAL SAFETY DATA SHEET

Date of issue: 2010-09-28

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name: Sealing strip based on EPDM rubber.

Supplier: Trelleborg Sealing Profiles Sweden AB
Box 1004, SE-331 29 Värnamo

Emergency phone number: +46 (0)370-48100

Information issued by: Per Mattsson

2. HAZARDS IDENTIFICATION

Vulcanised rubber is an article, not subject to classification.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Wt %
Rubber compound based on EPDM polymer	100

4. FIRST-AID MEASURES

Skin contact: Wash hands.

5. FIRE-FIGHTING MEASURES

Flammable/toxic gases will form upon decomposition.
Extinguish the fire by cooling with water spray.

6. ACCIDENTAL RELEASE MEASURES

Recover spilled material and place in suitable containers for recycle or disposal.

7. HANDLING AND STORAGE

No special protective measures required.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Observe standard industrial hygiene practices for handling.

Use protective cream.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical form: Solid and/or cellular rubber

Colour: Black (white, brown or grey)

Odor: Typical rubber

Decomposition temperature > 250 °C

Density (g/cm³) 0,25 - 1,40

10. STABILITY AND REACTIVITY

Decomposition temperature over 250°C.

11. TOXICOLOGICAL INFORMATION

Inhalation: No hazard under 100°C.

Skin contact: No hazard at industrial handling.

12. ECOLOGICAL INFORMATION

Insoluble in water.

13. DISPOSAL CONSIDERATIONS

Dispose according to local regulations.

14. TRANSPORT INFORMATION

Not regulated

15. REGULATORY INFORMATION

No classification

16. OTHER INFORMATION